

chlorine taste and odor, cyst and lead reduction.

Each block is wrapped with a polypropylene outer layer and netting to prevent premature clogging of the carbon block. All materials and components are FDA-compliant, making them ideal for use in residential, food service and commercial drinking water applications.

Features & Benefits

- 100% coconut shell carbon
- · Nominal 0.5 micron rating
- Low pressure drop
- Temperature range 40-170°F (4.4-74.7°C)
- Exceptional Chlorine taste and Odor Reduction
- Lead Reduction
- · Copper Reduction
- · Cyst Reduction Giardia Lamblia, Cryptosporidium, Toxoplasma, Entomoeba
- Turbidity Reduction



USATECH PLUSPB



Part Number	Nominal Dimensions	Lead Capacity*	Initial Pressure Drop* (PSI)
CB2510CL01	2.5"x10"	2,500gals@0.75GPM	<10psi@1GPM
CB2520CL01	2.5"x20"	5,000gals@1.50GPM	<10psi@2GPM
CB4510CL01	4.5"x10"	8,000gals@2GPM	<7psi@3GPM
CB4520CL01	4.5"x20"	16,000gals@4GPM	<7psi@6GPM



Important Notice

Performance claims are based on a complete system. The filter must be used in an approved system and operating according to the system's specifications. Each application must be followed in order for the filter to perform properly.

Warnings

Usatech Carbon Block filters are to only be used with microbiologically safe water. The filter is not designed to kill or remove bacteria or viruses. All information is based on data believed to be reliable. This information is offered for verification and evaluation only and is not intended to be a warranty.

